



Pristine Clean Bags[®] LDPE

Typical Properties Data sheet

All testing performed on 1mil thick film.

Property	Nonminal Value	Test Method
Density	0.923 g/cm ³	ASTM D792
Melt Index	1.9g/10min	ASTM D1238
Film Toughness	MD 2220 ft-lb/in ³	ASTM D882
	TD 2290 ft-lb/in ³	
Tensile Strength	MD Yield 1740 psi	ASTM D882
	TD Yield 1780 psi	
	MD Break 3600psi	
	TD Break 3010psi	
Tensile Elongation	MD Break 520%	ASTM D882
	TD Break 720%	
Dart Drop Impact	100g	ASTM 1709A
Elmendorf Tear strength	MD 560g	ASTM 1922
	TD470g	

- 21 CFR177.1520(c), paragraph 2.2 compliant
- European Commission (EU) No 10/2011 compliant as of 4/9/2012.
- Components of animal origin have not been knowingly added to this product.
- This product is not manufactured with any of the Substances on Very High Concern (SVHC).
- Complies with the requirements of Article 4.1 of EU Directive 2011/65/EU (RoHS)
- This product is not intentionally manufactured with Bisphenol A, natural rubber, natural latex, Phthalates, Fluorotelomers, Perfluorooctanoic acid (PFOA) or Perfluorooctane sulfonate (PFC)
- Complies with California Proposition 65

Notice: All statements, information and data given herein are believed to be reliable, but are presented without guarantee, warranty or responsibility of any kind, expressed or implied. The values presented in this data sheet are typical and are not to be interpreted as product specifications.